

XPand6227

End of Life

Intel® Xeon® D-1500 Family Processor-Based Rugged Small Form Factor (SFF) COTS System with 14-Port Gigabit Ethernet Switch & Router with Cisco IOS®

Please contact X-ES Sales

- ▶ 11 10/100/1000BASE-T Gigabit Ethernet switch ports
- ▶ Three 10/100/1000BASE-T Gigabit Ethernet router ports
- ▶ Two 10/100/1000BASE-T Gigabit Ethernet SBC ports
- ▶ Includes one XPedite7672 Intel® Xeon® D-1500 family-based 3U VPX SBC
- ▶ Includes one XChange3013 Gigabit Ethernet switch with Layer 2/3 management
- ▶ Includes one XPedite5205 Cisco IOS® Gigabit Ethernet Embedded Services Router (optional)
- ▶ XPedite5205 is NIST FIPS 140-2 Overall Level 1 validated on certificate #2242 and NIAP Common Criteria certified
- ▶ Layer 2 switching and Layer 3 routing management with extensive IEEE protocol and IETF RFC support (optional)
- ▶ VICTORY Infrastructure Switch and Router support (optional)
- ▶ Supports one removable memory module
- ▶ Small Form Factor (SFF) sub-½ ATR system
- ▶ Conduction- or convection-cooled chassis
- ▶ Integrated 28 VDC power supply
- ▶ MIL-STD-461E/F, MIL-STD-810, MIL-STD-704F qualified
- ▶ Environmentally sealed
- ▶ Circular connector support



XPand6227

The XPand6227 is a true Commercial-Off-The-Shelf (COTS) rugged system based on the Intel® Xeon® D-1500 family (formerly Broadwell-DE) of processors and a Gigabit Ethernet switch optionally hosting an XPedite5205 Cisco IOS® Gigabit Ethernet Embedded Services Router. With a compact design, the XPand6227 maximizes processing and networking performance while providing a SWaP-optimized alternative to traditionally larger slot-based systems; it is an actual Small Form Factor (SFF) system based on COTS 3U VPX modules.

The XPand6227's first slot supports the XPedite7672 Intel® Xeon® D-1500 family-based 3U VPX SBC. The XPand6227's second slot supports the XChange3013 3U VPX Gigabit Ethernet switch. The XChange3013 can be configured as a fully managed Layer 2 switch or Layer 3 router. The XChange3013 delivers full wire-speed across all of its ports and supports jumbo packets up to 12 kB. It supports IPv6 and a comprehensive set of IETF RFCs and IEEE protocols. The XChange3013 optionally supports compliance with the VICTORY specification as an Infrastructure Switch and Router. The XPedite5205 Cisco IOS® Router XMC can optionally be installed on the XChange3013 to provide highly secure data, voice, and video communications to stationary and mobile network nodes. The system supports a memory module bay to host a removable SATA Solid-State Drive (SSD) flash memory module.

The XPand6227 supports the rear I/O from the installed VPX modules with two 130-pin circular connectors. This fully ruggedized system is designed to meet the rigorous standards of MIL-STD-810 and DO-160, while integrating the latest power-saving and performance-enhancing technology. The heat from the internal conduction-cooled modules is conducted to sidewall heat exchangers, where it is dissipated to the ambient environment by convection cooling or to an attached cold plate by conduction cooling. The system includes an integrated MIL-STD-704 28 VDC power supply and MIL-STD-461 EMI filtering.

X-ES

Extreme Engineering Solutions

*“Fast, Flexible, Customer-Focused
Embedded Solutions”*

Extreme Engineering Solutions

9901 Silicon Prairie Parkway • Verona, WI 53593
Phone: 608.833.1155 • Fax: 608.827.6171
sales@xes-inc.com • <https://www.xes-inc.com>

Physical Characteristics

- Chassis dimensions and weight are dependent on configuration; contact factory for assistance

Ethernet Management Features (Optional)

- Layer 2 switching and Layer 3 routing
- Extensive IEEE protocol and IETF RFC support
- Configuration through CLI or SNMP
- 196 MB packet buffer
- VICTORY Infrastructure Switch and Router support
- XPedite5205 Cisco IOS® Gigabit Ethernet Embedded Services Router XMC

Ethernet Switch Features

- IPv4 and IPv6 support
- Support for jumbo frames up to 12 kB
- Advanced cable open/short detection
- Non-blocking, full wire-speed
- IEEE 1588v2 and SyncE support (optional)

First Slot I/O (XPedite7672)

- Two 10/100/1000BASE-T Gigabit Ethernet ports to J2
- One RS-232 port to J2
- Two USB 2.0 ports to J2

Second Slot I/O (XChange3013 and XPedite5205)

- 10 10/100/1000BASE-T Gigabit Ethernet switch ports to J3
- Three 10/100/1000BASE-T Gigabit Ethernet router ports to J3
- One 10/100/1000BASE-T Gigabit Ethernet switch port to J2
- Two RS-232 ports to J3

Slot-to-Slot Connectivity

- Two 1000BASE-X Gigabit Ethernet ports

Removable Memory Bay

- Supports one X-ES ruggedized 2.5 in. Solid-State Drive (SSD) with optional intergrated encryption
- Up to 512 GB of SLC NAND flash

Power Supply

- Integrated power supply
- MIL-STD-704 28 VDC input voltage support
- MIL-STD-461 EMI filtering

Thermal

- The system is designed and tested to operate in ambient temperatures down to -40°C and extreme high temperatures. Maximum operating temperature is dependent on configuration and usage. Contact X-ES for further information.

