

XPedite5972

NXP QorIQ T2080 Processor-Based Conduction- or Air-Cooled 3U VPX Module

- ▶ NXP QorIQ T2080 processor with eight virtual Power Architecture® e6500 cores at up to 1.8 GHz
- ▶ 128-bit AltiVec technology-based SIMD engine
- ▶ Compatible with multiple VITA 65 OpenVPX™ slot profiles
- ▶ 3U VPX (VITA 46) module
- ▶ Ruggedized Enhanced Design Implementation (REDI)
- ▶ Conduction or air cooling
- ▶ Up to 8 GB of DDR3 ECC SDRAM
- ▶ Up to 512 MB of NOR flash (with redundancy)
- ▶ Up to 64 GB of NAND flash
- ▶ Hardware write protection for non-volatile memory
- ▶ XMC/PrPMC interface
- ▶ x4 PCI Express or Serial RapidIO or 10 GbE XAUI fabric Fat Pipe P1.A fabric interconnect
- ▶ x4 PCI Express or Serial RapidIO Fat Pipe P1.B fabric interconnect
- ▶ Two SerDes Gigabit Ethernet Thin Pipe P1 fabric interconnects
- ▶ Two 10/100/1000BASE-T Ethernet ports (optional)
- ▶ Two SATA ports to P2 or J16 (optional)
- ▶ Up to two RS-232/422/485 serial ports to P2
- ▶ Two USB 2.0 ports to P2 (optionally, can route one port to front panel via plugover module)
- ▶ Front I/O available via plugover module
- ▶ Linux BSP
- ▶ Wind River VxWorks BSP
- ▶ Green Hills INTEGRITY BSP
- ▶ DDC-I's DO-178 Certifiable Deos BSP



XPedite5972

The XPedite5972 is a 3U OpenVPX™ REDI single board computer based on the NXP QorIQ T2080 processor. It is a design refresh of the XPedite5970, intended to update obsolete components while maintaining the same functionality and features.

The XPedite5972 provides a rugged, feature-rich processing solution that maximizes the performance-per-watt capabilities of a Power Architecture®-based processor module. The T2080 processor offers eight virtual (four dual-threaded) e6500 cores, running at up to 1.8 GHz, and integrates a 128-bit AltiVec technology-based SIMD engine per core. The integrated AltiVec SIMD engines enable the XPedite5972 to support DSP-level Floating-Point performance and an extensive inventory of software libraries.

The XPedite5972 also supports up to 8 GB of DDR3 ECC SDRAM and provides a plethora of I/O options to the backplane, including 10 Gigabit Ethernet, PCI Express Gen3, and Gen2 SRIO. The XPedite5972 provides superior growth and expansion capabilities by including an XMC or PMC site with full 10 mm I/O envelope support while maintaining a 0.8 in. VPX slot pitch, providing the system integrator with a wide variety of COTS options for additional I/O, storage, or processing while minimizing total system SWaP-C.

Wind River VxWorks, Linux, Green Hills INTEGRITY, and DDC-I's DO-178 Certifiable Deos Board Support Packages (BSPs) are available.



Extreme Engineering Solutions

*“Fast, Flexible, Customer-Focused
Embedded Solutions”*

Extreme Engineering Solutions

9901 Silicon Prairie Parkway • Verona, WI 53593
Phone: 608.833.1155 • Fax: 608.827.6171
sales@xes-inc.com • <https://www.xes-inc.com>

Processor

- NXP QorIQ T2080 processor
- Eight virtual (four dual-threaded) Power Architecture® e6500 cores at up to 1.8 GHz
- 2 MB L2 cache
- 512 kB platform cache
- IEEE 754 Floating-Point Unit (FPU) support
- 128-bit Altivec technology-based SIMD engine

Memory

- Up to 8 GB of DDR3 ECC SDRAM
- Up to 512 MB of NOR flash (with redundancy)
- Up to 64 GB of NAND flash

XMC/PrPMC Site

- 32-bit, 66 MHz PCI bus (PMC interface)
- x4 PCI Express port (XMC interface)
- P64s P14 I/O support (optional)
- X12d P16 I/O support

Front Panel I/O

- Front panel RJ-45 Ethernet, micro-DB-9 RS-232 serial ports, and USB 2.0 available via optional plugover module

VPX (VITA 46) P0 I/O

- I²C port

VPX (VITA 46) P1 I/O

- x4 PCI Express, Serial RapidIO or 10 GbE XAUI Fat Pipe to P1.A
- x4 PCI Express or Serial RapidIO Fat Pipe to P1.B
- Two SerDes Gigabit Ethernet ports (or one 10/100/1000BASE-T port to P1 and one 10/100/1000BASE-T port to P2)
- X12d XMC P16 I/O

VPX (VITA 46) P2 I/O

- One 10/100/1000BASE-T port (when two SerDes Gigabit Ethernet P1 ports are not used)
- Two RS-232/422/485 serial ports
- Two USB 2.0 ports
- I²C port
- 3.3 V GPIO signals
- P64s PMC P14 I/O (optional)
- Two SATA ports capable of 6 Gb/s (optional)

Software Support

- Wind River VxWorks BSP
- Linux BSP
- Green Hills INTEGRITY-178 BSP
- DDC-I's DO-178 Certifiable Deos BSP
- Contact factory for availability of QNX Neutrino and LynxWorks LynxOS BSPs

Physical Characteristics

- 3U VPX-REDI conduction- or air-cooled form factor
- Dimensions: 100 mm x 160 mm
- 0.8 in. pitch without solder-side cover
- 0.85 and 1.0 in. pitch with solder-side cover

Environmental Requirements

Contact factory for appropriate board configuration based on environmental requirements.

- Supported ruggedization levels (see chart below): 5
- Conformal coating available as an ordering option
- Contact X-ES for air-cooled development options

Power Requirements

- Power will vary based on configuration and usage. Please consult factory.

Ruggedization Level	Level 5
Cooling Method	Conduction-Cooled
Operating Temperature	-40 to +85°C (board rail surface)
Storage Temperature	-55 to +105°C (maximum)
Vibration	0.1 g ² /Hz (maximum), 5 to 2000 Hz
Shock	40 g, 11 ms sawtooth
Humidity	Up to 95% non-condensing

