

XPort3200

End of Life

Freescale QorIQ P1020 Processor-Based Conduction- or Air-Cooled XMC/PMC IEEE 1588v2 Grandmaster Clock Module

Please contact X-ES Sales

- › Freescale QorIQ P1020 processor with dual PowerPC e500v2 cores at 800 MHz
- › Conduction or air cooling
- › Extended shock and vibration tolerance
- › 1 GB of DDR3 ECC SDRAM
- › x4 PCI Express or serial RapidIO interface to P15
- › PCI PrPMC interface
- › Two Gigabit Ethernet ports to P14 or P16
- › Two RS-232/422/485 serial ports to P14 or P16
- › One USB 2.0 port
- › 256 MB of NOR flash (with redundancy)
- › 16 GB of NAND flash
- › IEEE 1588v2 ordinary clock
- › IEEE 1588v2 boundary clock
- › 1 PPS and configurable frequency output
- › 1 PPS and reference frequency input (optional)
- › High-precision oven-controlled oscillator (OCXO)
- › GPS support (optional)
- › Linux BSP



XPort3200

The XPort3200 is a rugged, IEEE 1588v2 Precision Time Protocol (PTP) ordinary clock with grandmaster capabilities. Hardware options range from commercial/air-cooled to full-military conduction-cooled solutions.

The XPort3200 is capable of providing nanosecond-level time and frequency synchronization for Ethernet networks. Support for multicast and optional unicast packets, along with grandmaster and slave operation, provide a complete IEEE 1588v2 solution.

1 PPS and input clock synchronization, as well as configurable clock and 1 PPS outputs, allow for synchronizing the grandmaster to an external time reference or providing a frequency reference to an external device.

X-ES

Extreme Engineering Solutions

*“Fast, Flexible, Customer-Focused
Embedded Solutions”*

Extreme Engineering Solutions

9901 Silicon Prairie Parkway • Verona, WI 53593
Phone: 608.833.1155 • Fax: 608.827.6171
sales@xes-inc.com • <https://www.xes-inc.com>

Processor

- Freescale QorIQ P1020 processor
- Dual PowerPC e500v2 cores at 800 MHz
- 256 kB of shared L2 cache

IEEE 1588v2

- Ordinary clock support
- Boundary clock support
- Grandmaster support
- Multicast synchronization support
- Unicast synchronization support (optional)
- Nanosecond-level resolution
- On-card GPS time synchronization (optional)

Memory

- 1 GB of DDR3 SDRAM
- 256 MB of NOR flash (with redundancy)
- 16 GB of NAND flash

Synchronous Ethernet

- Support for distributing clock over Ethernet
- Support for recovering Ethernet clock connection

PrPMC Interface

- 66/33 MHz PCI
- 32-bit bus interface

P15 XMC Interface

- x4 configurable PCI Express or Serial RapidIO

P14/P16 XMC/PMC Interface

- Two Gigabit Ethernet ports
- Two RS-232/422/485 ports
- 3.3 V GPIO
- One USB 2.0 port
- 1 PPS and reference frequency input (optional)
- 1 PPS and configurable clock output

Software Support

- Linux BSP

Physical Characteristics

- Conduction- or air-cooled XMC/PMC form factor
- Dimensions: 143.75 mm x 74 mm, 10 mm stacking height

Environmental Requirements

Contact factory for appropriate board configuration based on environmental requirements.

- Supported ruggedization levels (see chart below): 1, 3, 5
- Conformal coating available as an ordering option

Power Requirements

- Power will vary based on configuration and usage. Please consult factory.

Ruggedization Level	Level 1	Level 3	Level 5
Cooling Method	Standard Air-Cooled	Rugged Air-Cooled	Conduction-Cooled
Operating Temperature	0 to +55°C ambient †	-40 to +70°C ambient †	-40 to +85°C (board rail surface)
Storage Temperature	-40 to +85°C ambient	-55 to +105°C ambient	-55 to +105°C (maximum)
Vibration	0.002 g ² /Hz (maximum), 5 to 2000 Hz	0.04 g ² /Hz (maximum), 5 to 2000 Hz	0.1 g ² /Hz (maximum), 5 to 2000 Hz
Shock	20 g, 11 ms sawtooth	30 g, 11 ms sawtooth	40 g, 11 ms sawtooth
Humidity	Up to 95% non-condensing	Up to 95% non-condensing	Up to 95% non-condensing

† Contact factory for airflow rate details.

